

419Ph 22" TFT MONITOR



Panel	24" (61 cm) TFT Active Matrix
Design Line	Professional Wide
Pixel / Dot Pitch	0.270 x 0.270 mm
Viewable Image Size (Diagonal)	24"
Display Area	518.4 x 324 mm
Brightness	400 cd/m ² (typ.)
Contrast Ratio	6000:1 (DCR)
Typ. Response Time (tr)	5 ms
Viewing Angle	CR(>=10):160/160;Degrees
Compatibility	VESA,VGA,SVGA,XGA,SXGA,Mac®
Scanning Frequency	H:24~83KHz V:56~76Hz
Pixel Frequency	170MHz(max)
Maximum Resolution	1920 x 1200@60Hz
Recommended Resolution	1920 x 1200@60Hz
Resolution Supported	640x480@60/67/72/75Hz, 720x400@70Hz, 800x600@56/60/72//75Hz, 832x624@75Hz 1024x768@60/70/75Hz 1152x870@75Hz 1280x720@60, 1280x960@60, 1280x1024@60/75Hz 1440x900@60Hz
Colours	16.7 M
Signal Input	Analog,DVI-D, HDMI,USB
Connectors	15-pin D-Sub & 24-pin_DVI-D&HDMI&USB
Power Source	Power Input: Universal 110~240VAC, 50/60Hz
Power Consumption	On: <64W , Stabdy: <2 W
Plug & Play	DDC 1/2B/CI or VESA DDC2B™
EPA ENERGY STAR®	
User Control	Auto,Eco/up,Down, Menu,Power,SOURCE
Function	Brightness, Contrast, Eco Mode,Gamma(1,2,3),DCR,Focus, Clock, H/V Position, Color Temperature, Color Boost, Picture Boost, OSD Setup, Extra, Reset , Exit
OSD Languages	9 languages
Speaker	2 x 3 Watt
Emissions Standard	
Regulation	UL, FCC, CE, EPA, CCC,UL,ISO13406-2 type2, TC003, Windows Vista Premium, RoHS
Other Features	VESA 100mm Wall Mountable, Kensington Security Slot, -5-20° Tilt, 90° Pivot, 110mm Adjustment Base
Dimensions (WxHxD)	Monitor: 562.8 x 458.4 x 240 / Carton:622 x 525 x 162
Weight	Net: 6.65kg / Gross: 8.88kg
Loading Qty w/pallet	40" 1064pcs 20" 504pcs
Warranty	3 Year Parts & Labor
EAN Code	4038989140369

Note: Specifications are subject to change without notice. *Wall mount arm & bracket not included.

SPECIFICATIONS

