



# 619Fh 26" TFT MONITOR

<b>Panel</b>	26" (64.8 cm) TFT Active Matrix LCD
<b>Design Line</b>	<b>Fashion Wide</b>
<b>Pixel / Dot Pitch</b>	0.2865_0.2865 mm
<b>Viewable Image Size (Diagonal)</b>	26"
<b>Display Area</b>	550.08x343.8mm
<b>Brightness</b>	400 cd/m <sup>2</sup> (typ.)
<b>Contrast Ratio</b>	4000:1 (DCR)
<b>Typ. Response Time (tr)</b>	3ms
<b>Viewing Angle</b>	CR(>=10):160/160;Degrees
<b>Compatibility</b>	VESA,VGA,SVGA,XGA,SXGA,Mac®
<b>Scanning Frequency</b>	H:24~83KHz V:56~76Hz
<b>Pixel Frequency</b>	170MHz(max)
<b>Maximum Resolution</b>	1920x1200@60Hz
<b>Recommended Resolution</b>	1920x1200@60Hz
<b>Resolution Supported</b>	640x480@60/67/72/75Hz, 720x400@70Hz, 800x600@56/60/72//75Hz 832x624@75Hz, 1024x768@60/70/75Hz 1152x870@75Hz, 1280x720@60 1280x960@60, 1280x1024@60/75Hz, 1440_900@60Hz 1600x1200@60Hz, 1680x1050@60Hz, 1920x1200@60Hz
<b>Colours</b>	16.7M
<b>Signal Input</b>	Analog,DVI-D, HDMI,USB
<b>Connectors</b>	15-pin D-Sub & 24-pin_DVI-D&HDMI&USB
<b>Power Source</b>	Power Input: Universal 110~240VAC, 50/60Hz
<b>Power Consumption</b>	On: <120W , Stabdy: <2 W
<b>Plug &amp; Play</b>	DDC 1/2B/CI or VESA DDC2B™
<b>EPA ENERGY STAR®</b>	
<b>User Control</b>	Auto,Eco/up,Down, Menu,Power,SOURCE
<b>Function</b>	Brightness, Contrast, Eco Mode,Gamma(1,2,3),DCR,Focus, Clock, H/V Position, Color Temperature, Color Boost, Picture Boost, OSD Setup, Extra, Reset , Exit
<b>OSD Languages</b>	2008 new 8 languages
<b>Speaker</b>	2 x 3 Watt
<b>Emissions Standard</b>	
<b>Regulation</b>	UL, FCC, CE, EPA, CCC,UL,TUVGS,GOST ISO13406-2 type2, Windows Vista Premium, RoHS
<b>Other Features</b>	VESA 100 mm Wall Mountable, Kensington Security Slot, -5-22° Tilt
<b>Dimensions (WxHxD)</b>	Monitor: 605x240x472.8 / Carton:690x188x566
<b>Weight</b>	Net: 7.75kg / Gross: 10.8kg
<b>Loading Qty w/pallet</b>	40" 748pcs 20" 352pcs
<b>Warranty</b>	3 Year Parts & Labor
<b>EAN Code</b>	4038989160305

Note: Specifications are subject to change without notice. \*Wall mount arm & bracket not included.

## SPECIFICATIONS

