

# 919P2 19" TFT MONITOR



<b>Panel</b>	19" (48.1 cm) TFT Active Matrix LCD
<b>Design Line</b>	
<b>Pixel / Dot Pitch</b>	0.294mm x 0.294mm
<b>Viewable Image Size (Diagonal)</b>	19"
<b>Display Area</b>	376.32 x 301.056 mm
<b>Brightness</b>	300 cd/m <sup>2</sup> (typ.)
<b>Contrast Ratio</b>	10000:1 (DCR)
<b>Typ. Response Time (tr)</b>	2ms
<b>Viewing Angle</b>	CR> 10: 170/160 Degrees
<b>Compatibility</b>	
	VESA,VGA,SVGA,XGA,SXGA,Mac®
<b>Scanning Frequency</b>	
	H:30~80KHz V:55~75Hz
<b>Pixel Frequency</b>	
	135M
<b>Maximum Resolution</b>	
	1280 x 1024@75Hz
<b>Recommended Resolution</b>	
	1280 x 1024@75Hz
<b>Resolution Supported</b>	
	640x480@60/67/72/75Hz; 800x600@56/60/72/75Hz; 1024x768@60/70/72/75Hz; 1280x1024@60/75Hz
<b>Colours</b>	
	16.7M
<b>Signal Input</b>	
	Analogue: D-Sub Digital Input: DVI-D
<b>Connectors</b>	
	Analogue RGB Signal: 15-pin D-sub DVI-D: 24-pin DVI-D
<b>Power Source</b>	
	Universal 110~240VAC, 50/60Hz
<b>Power Consumption</b>	
	On: <45W , Stand by: <2 W
<b>Plug &amp; Play</b>	
	DDC 1/2B/CI or VESA DDC2B™
<b>EPA ENERGY STAR®</b>	
<b>User Control</b>	
	Auto, Eco/up, Down, Menu, Power
<b>Function</b>	
	Brightness, Contrast, Eco Mode,Gamma(1,2,3),DCR,Focus, Clock, H/V Position, Color Temperature, Color Boost, Picture Boost, OSD Setup, AUTO Config, Reset,Information,Input select,Image Ratio,DDC/CI,Exit
<b>OSD Languages</b>	
	9 languages
<b>Speaker</b>	
	1 x 2 Watt
<b>Emissions Standard</b>	
<b>Regulation</b>	
	CUL, FCC, CE, TUV_bauart , EPA, TC003, ISO13406-2, VISTA PREMIUM
<b>Other Features</b>	
	VESA 100mm Wall Mount Compliant, Kensington Slot Security, 110mm Height Adjustment, -2~92°Pivot,-5~20° Tilt
<b>Dimensions (WxHxD)</b>	
	Monitor: 409 x 250 x 415 / Carton: 470 x 218 x 475
<b>Weight</b>	
	Net: 5.75Kg / Gross: N/A
<b>Loading Qty w/pallet</b>	
	40" 1100pcs 20" 528pcs
<b>Warranty</b>	
	3 Year Parts & Labor
<b>EAN Code</b>	
	4038989190326

Note: Specifications are subject to change without notice. \*Wall mount arm & bracket not included.

## SPECIFICATIONS

