

## LM2028



<b>Panel</b>	TFT Active Matrix LCD, Slim Cabinet VIS: 20.1" (51.0cm), Diagonal Hard Coating (3H), Anti-glare Treatment
<b>Design Line</b>	Design
<b>Pixel / Dot Pitch</b>	0.255mm x 0.255mm
<b>Viewable Image Size (Diagonal)</b>	20.1"
<b>Display Area</b>	408mm x 306mm
<b>Brightness</b>	300cdm2
<b>Contrast Ratio</b>	1000:1
<b>Typ. Response Time (tr+tf)</b>	8ms (GTG)
<b>Viewing Angle</b>	Horizontal: 178 Degrees Vertical: 178 Degrees
<b>Compatibility</b>	VESA, SXGA, XGA, SVGA, VGA Mac® Equipped With VGA Port
<b>Scanning Frequency</b>	Horizontal: 30K~80KHz (analogue) Vertical: 55~75 Hz
<b>Pixel Frequency</b>	135 MHz
<b>Maximum Resolution</b>	1600x1200
<b>Recommended Resolution</b>	1600x1200@60Hz
<b>Resolution Supported</b>	800x600@60/75Hz, 1024x768@60/75Hz, 1280x1024@60/75Hz, 1600x1200@60Hz
<b>Colours</b>	16.7M
<b>Signal Input</b>	Analogue: Video: 0.7Vp-p, RGB analogue Separate Sync: TTL Level H/V Sync: Positive / Negative <b>Digital Input: DVI-D (TMDS)</b>
<b>Connectors</b>	Analogue RGB Signal: 15-pin D-sub Male (Attached) <b>DVI-D: 24-pin DVI-D</b> Power: 3-pin Plug (CEE22)
<b>Power Source</b>	Power Input: Universal 100~240VAC, 50/60Hz
<b>Power Consumption</b>	60Watts (Max)
<b>Plug &amp; Play</b>	DDC1/2B
<b>EPA ENERGY STAR®</b>	Yes
<b>User Control</b>	Auto Adjust, Left Key, Right Key, Menu Key, On/Off Key
<b>Function</b>	Brightness, Contrast, Input Select, Focus, Clock, H/V Position, Language, Recall, Exit, RGB
<b>OSD Languages</b>	English, German, French, Spanish, Italian
<b>Speaker</b>	
<b>Emissions Standard</b>	TC099
<b>Regulation</b>	UL, CSA, FCC, TUV/GS, CE, ISO 13406-2, Pixel Fault Class II, Windows® XP Logo
<b>Other Features</b>	VESA 100mm Wall Mountable*, High Adjustment 80mm, Kensington Security Slot
<b>Dimensions (WxHxD)</b>	Monitor: 344-417x446x246 Carton: 225x516x425
<b>Weight</b>	NNet: 7.5kgs Gross: 9.5kgs
<b>Loading Qty w/pallet</b>	20' = 550 pcs 40' = 1150 pcs
<b>Warranty</b>	3 Years Parts & Labour

Note: Specifications are subject to change without notice.