

# I NEED SPECIFICATIONS



<b>CRT</b>	Size (Diagonal): 17" (43.2cm) Pure Flat
<b>Dot Pitch</b>	0.21mm(H) x 0.25mm(D)
<b>Viewable Image Size (Diagonal)</b>	16.0inches 406mm
<b>Display Area</b>	Pre-Set: 300mm x 230mm
<b>Compatibility</b>	VESA, XGA, SVGA, VGA
<b>Scanning Frequency</b>	Horizontal: 30K~72KHz
<b>Pixel Frequency</b>	110MHz
<b>Maximum Resolution</b>	1280x1024@60Hz
<b>Resolutions Supported</b>	640x350@70Hz, 720x400@70Hz, 640x480@60/72/75/85Hz, 800x600@60/72/75/85Hz, 1024x768@60/70/75/85Hz, 1280x1024@60/75/85Hz
<b>Colour</b>	Unlimited
<b>Signal Input</b>	Video: 0.7Vp-p, RGB analogue
<b>Connectors</b>	Video Signal: 15-pin D-sub Male (Attached)
<b>Power Source</b>	Universal 100~240 Vac, 50Hz / 60Hz
<b>Power Consumption</b>	120Watts (Max)
<b>Plug &amp; Play</b>	VESA DDC1/2B
<b>User Control</b>	Front Panel: OSD Shuttle Knob, Standby Power Key
<b>Function</b>	Contrast, Brightness, H-size, H-center, V-size, V-center, Zoom, Pincushion, Trapezoid, Pin-balance, Parallelogram, Rotation, 6500K, 9300K, User's Colour, Degauss, H/V Moire Reduce, Recall, Language, Exit
<b>OSD Languages</b>	English, German, French, Spanish, Italian, Portuguese
<b>Speaker</b>	Speaker base SPK22 with 2x1Watt, Power on/off, Volume, Earphone Output (CRT-Speaker base optional)
<b>Emissions Standard</b>	MPRII
<b>Regulations</b>	UL, FCC, FDA, CSA, TUV / GS
<b>Dimensions (WxHxD mm)</b>	Monitor: 410x402x420 Carton: 540x537x570
<b>Dimensions (WxHxD inches)</b>	Monitor: 16x15.7x16.4 Carton: 21.2x21.2x19.5
<b>Weight</b>	Net: 35.2lbs (16.0kgs); Gross: 42.9lbs (19.5kgs)
<b>Loading Qty w/ pallet</b>	20' = 160 pcs 40' = 352 pcs 40' HQ = 435 pcs
<b>Warranty</b>	3 Years Parts & Labour

**Note:** Specifications are subject to change without notice.